

Therma Waterproof Thermometer

with interchangeable thermocouple probes

- robust waterproof case offering IP66/67 protection
- backlight, max/min & hold functions
- integrated rubber seal for durability
- 2 year guarantee

The Therma Waterproof thermometer is housed in a robust waterproof black ABS case which offers IP66/67 protection. The thermometer utilises state of the art electronic circuitry, designed for reliability and ease of use and can be submerged or washed under a running tap - ideal for industrial applications.

The thermometer measures temperature over the range of -99.9 to 299.9 °C with a 0.1 °C resolution, auto-ranging to 1 °C resolution over the range of 300 to 1372 °C.

The Therma Waterproof thermometer features a large easy to read, LCD display with max/min, hold, open circuit, low battery indication and an optional backlight. The unit also incorporates an auto-power off facility that automatically turns the instrument off after ten minutes, maximising battery life.

Each unit is housed in a durable, ABS case that incorporates an integrated rubber seal to ensure complete water tightness and help reduce the possibility of damage in harsh environments.

We offer an extensive range of interchangeable type K thermocouple probes, for a variety of different applications, see pages 59 to 64 for full details.




optional accessories

- protective silicone boot. Various colours are available - see page 38 for details
- Probe Wipes - these anti-bacterial wipes are ideal for probes and everyday work surfaces - see page 35



order code	description
232-101	Therma Waterproof
830-257	protective silicone boot - black
832-015	stainless steel wall bracket

the Therma Waterproof is exclusive of probe



specification	Therma Waterproof
range 0.1 °C	-99.9 to 299.9 °C
range 1 °C	300 to 1372 °C
resolution	0.1 °C to 299.9 °C thereafter 1 °C
accuracy	±0.4 °C ±0.1 % of reading
battery	3 x 1.5 volt AAA
battery life	minimum 5 years (10000 hours)
sensor type	K thermocouple
display	15 mm LCD
dimensions	32 x 71 x 141 mm
weight	220 grams

FREE traceable certificate of calibration included